

U.S. PATENT APPLICATION

Inventor(s): MICHAEL BASARA

Invention: BOX-LIKE CONTAINER WITH AN INTERPENETRATING STRUCTURE
AND PROCESS FOR THE REALIZATION THEREOF

***NIXON & VANDERHYE P.C.
ATTORNEYS AT LAW
1100 NORTH GLEBE ROAD
8TH FLOOR
ARLINGTON, VIRGINIA 22201-4714
(703) 816-4000
Facsimile (703) 816-4100***

SPECIFICATION

BOX-LIKE CONTAINER WITH AN INTERPENETRATING STRUCTURE
AND PROCESS FOR THE REALIZATION THEREOF

ABSTRACT

5 A box-like hollow body, particularly a container of
various shapes and size, comprising at least an inner
hollow body 3 and an outer hollow body 2,
interpenetrating with each other so as to create an
integral structure with particular characteristics of
mechanical resistance and ornamental, and provided with
10 a continuous inner surface without gaps and an outer
surface patterned according to zones or sections.

DESCRIPTION

The present invention relates to a box-like hollow body, particularly a container of various shapes and size, comprising at least an inner hollow body and an
5 outer hollow body interpenetrating with each other so as to create a structure with particular characteristics of mechanical resistance and ornamental, and provided with a continuous inner surface without gaps and an outer surface patterned
10 according to zones or sections.

The present invention further relates to a process for the realization of said hollow body.

Containers or box-like bodies, in particular containers such as glasses, soup-tureens, jugs, boxes for
15 alimentary products and the like are known that have a double wall and a decoration visible on the surface.

Such box-like bodies are generally constituted by an inner body on whose outer surface a decoration or a pattern is obtained and by an outer body from
20 transparent material which coats and covers the inner body and which is obtained by casting or injection on or about the inner body. As the external body is realized from transparent material, the decoration or the pattern obtained on the external wall of the inner

body is visible in transparency through the thickness of the external body.

To realize such box-like hollow bodies, like plastic material cups or the like, according to the known art,

- 5 a first shell or hollow body is prepared, for instance by injection. Then, on such first shell a second shell is also realized by injection on the outside or in the inside of the first shell, said second shell being caused to adhere to the wall of the first shell; or,
- 10 the two shells are prepared separately, so that one of them is exactly contained in the other one, and so molded as to cause the two shells to adhere to one another.

- Said known containers have the disadvantage that they
- 15 are substantially constituted by two containers located one inside the other and that the more external container is made from a transparent material.

Besides, in case of knock or fall of the container, the two bodies tend to detach from one another.

- 20 Object of this invention is to provide a box-like hollow body, in particular a container of various shapes and size, provided with an outer surface with variously decorated or colored zones or sectors,

perfectly matching with each other and affording an agreeable and original visual effect.

A further object of the invention is to provide a box-like hollow body, made in particular from plastic material, comprising at least two hollow bodies intimately associated to each other, in such a way as not to be detachable from each other because of knocks or other stresses.

These and still other objects and the related advantages that will be made apparent from the following description are achieved by a box-like body, particularly a container of various shapes and size, such as a cup, jar, box, glass, jug and the like, which container, according to the present invention, comprises at least a first outer hollow body and a second inner hollow body, interpenetrating with each other so as to form an integral structure provided with a continuous inner surface without any gaps, and an outer surface with zones or sectors constituted by portions of said second inner hollow body emerging on the surface of said first outer hollow body in such a way as to form a substantially continuous, variously decorated outer surface.

More particularly, said first outer hollow body is provided with apertures such as holes, windows, cuttings and the like, variously located and having various shapes and size, and said second inner hollow
5 body is realized in the inside of said first outer body and is provided with a continuous inner surface and an outer surface having raised portions with shape, size and thickness corresponding to the shape, size and thickness of said apertures, said raised portions being
10 realized within said apertures and peripherally exactly and intimately matching the edge of said apertures.

Besides, the edges of said apertures obtained in said first outer hollow body are preferably realized at an acute angle, so as to ensure a still better
15 interpenetration and coupling stability between said apertures and said raised portions of said second inner hollow body.

The box-like hollow body according to the present invention may be realized from different materials such
20 as, for instance, plastic materials or glass. In particular, any material may be used that is suitable to change its physical state from a flowing fluid during the working step to a solid in the finished product.

Advantageously, a process for the realization of said box-like hollow body comprises the following steps:

- realization of said first outer hollow body provided with said apertures by casting or injection of a first material into a suitable mold having the selected shape,

- casting or injection of a second material, compatible with said first material, into the inside of said first outer hollow body placed in a suitable mold, so that said second material forms said second inner hollow body, filling said apertures and realizing said continuous inner surface and forming an integral structure with said first hollow body.

The invention is described hereafter with reference to the attached drawings, reported by way of non limiting illustration of the invention, wherein:

- Figure 1 shows a schematic perspective view of the first hollow body,
- Figure 2 schematically shows the box-like hollow body according to the invention, comprising the first hollow body and the second hollow body,
- Figure 3 schematically shows a section of the box-like hollow body of Figure 2,

- Figure 4 schematically shows a section of a variant of the box-like hollow body according to the present invention.

With reference to such figures, the box-like hollow body 1 according to the invention comprises a first outer hollow body 2 and a second inner hollow body 3. The first hollow body 2 is provided with apertures constituted by windows 4 and 4a and by cutting 4b, within which apertures are respectively housed the raised portions 5, 5a and 5b of the second inner hollow body 3.

The edges 11, 12, 13 of the apertures obtained in said first outer hollow body 2 are realized at an acute angle. This realization is possible thanks to the process according to the present invention, and is very advantageous as it ensures a perfect and indissoluble coupling between the first body and the second body.

According to a variant of the present invention, said box-like hollow body comprises a first outer hollow body 6, a second intermediate hollow body 7 and a third inner hollow body 8.

In this way it is possible to realize an outer surface of the box-like body constituted by zones divided by the emerging on the surface of the outer hollow body 6

of the raised portions 9 of the intermediate hollow body 7 and the raised portions 10 of the inner hollow body 8, obtaining in this way special aesthetic effects.